

www.ngs.noaa.gov

# Historical National Vertical Datums in the United States

- Orthometric heights
  - Up to National Geodetic Vertical Datum of 1929 (NGVD 29)
  - North American Vertical Datum of 1988 (NAVD 88)
  - Defined through leveling network
- Ellipsoid heights
  - North American Datum of 1983 (NAD 83)
- Geoid Heights
  - GRS80/NAD 83
  - Gravity
  - GPS on bench marks

    XXIV FIG International Congress 2010



\_

www.ngs.noaa.go

#### NGS' Height Modernization Program

- Height Modernization Study 1998
  - Cost benefits
  - Pilot projects
  - Guidelines
- Assistance to states through Federal Funding
- Refining geoid height model to fit NAVD 88
- Goal: Improve access to vertical control

XIV FIG International Congress 2010

3

NOAA's National Geodetic Survey Positioning America for the Future

www.ngs.noaa.gov

# Problems Maintaining this kind of Vertical Datum

- Dependence on passive control
- Dynamic nature of Earth's surface
- Inherent error propagated on a national scale in leveling measurements
- Expense of monitoring network requires return to marks
- Maintaining multiple Datums can't level between islands/territories and conterminous U.S.

XXIV FIG International Congress 2010

www.ngs.noaa.gov

### Fixing NAVD 88

- Short term fix: Height Modernization GNSS surveys
  - Requires accurate geoid model
  - Requires minimal NAVD 88 control to get the model
- Long term fix: Re-level NAVD 88
  - Cost estimate between \$200 million and \$2 billion
- Fixes don't address many issues with the datum
- Third option Replace NAVD 88

XXIV FIG International Congress 2010

.

NOAA's National Geodetic Survey Positioning America for the Future

www.ngs.noaa.gov


#### When to Redefine a Datum

- When more observations/stations will improve the network accuracy/consistency
- When better field and adjustment procedures can improve results
- When deficiencies in the network make it distorted or inaccessible
- When better technology can give you more accurate data, or a better way to access datum

XXIV FIG International Congress 2010

www.ngs.noaa.gov

# GRAV-D: Gravity for the Redefinition of the American Vertical Datum



- Airborne Gravity Snapshot
- Absolute Gravity Tracking
- Re-define the Vertical Datum of the USA
- Target date 2018 per 10-year plan
- Target: 2 cm accuracy orthometric heights from GNSS and a geoid model

XXIV FIG International Congress 2010

7


NOAA's National Geodetic Survey Positioning America for the Future

www.ngs.noaa.gov

### Maintaining a datum - monitoring gravity

- Space based gravity data
- Repeat absolute and relative gravity
- Static in short term
- Update in long term
- Metadata includes epoch, velocities

XXIV FIG International Congress 2010



www.ngs.noaa.gov

#### Pros and Cons of the new Datum

- One consistent vertical datum spanning North America and US Territories
  - Canada also moving to Geoid based Datum
  - Mexico, Central America, Caribbean not planning on change yet but datum is available to them
- Datum is only accurate to 2 cm (4 cm network) at best at any given point (GNSS error + geoid error)
  - However, this is an improvement over NAVD 88 realization error
  - The datum could then be disseminated locally through very precise geodetic leveling

XXIV FIG International Congress 2010

www.ngs.noaa.gov

### Height Modernization: Transitioning to a New Datum

- Improve access to NAVD 88 today
  - Identify areas of immediate critical need
  - Build infrastructure that will help access today, and transformation tomorrow
- Prepare for transition to new vertical datum tomorrow
  - Models, tools, guidelines, specifications
  - Education, outreach, capacity building

XXIV FIG International Congress 2010

11

NOAA's National Geodetic Survey Positioning America for the Future

www.ngs.noaa.gov

# Achieving the mission through partnerships

- NGS maintains and monitors framework for defining Datums and accessing reference frame: Continuous GNSS stations (CORS) and gravity data
- Increasing reliance on partners, the user community, to maintain the passive control infrastructure to suit their needs
- NGS provides models, tools, guidelines, specifications, education
- NGS uses community-provided data to improve models


XXIV FIG International Congress 2010

www.ngs.noaa.gov

#### From NGS' 10-Year Plan

NGS Mission: "Modernize the Geopotential ("Vertical") Datum"

"The gravimetric geoid, long used as the foundation for hybrid geoid models, becomes *the most critical model produced by NGS.*"



XXIV FIG International Congress 201

